



## 275-140342 The Versatile One

Whether you want to sew smooth, displacement-free seams or seams with consistent or partial fullness - the lockstitch machine 275 always provides excellent sewing results of constant quality due to its differential foot top feed. The patented light-stroke feed system ensures superb climbing properties and an increased ruffling efficiency. Furthermore, it avoids feeding marks, even in the finest materials. The multitude of available sewing equipment and guide attachments makes the 275 a universal solution for high-quality seams in all sectors of the clothing industry. With direct drive.





## 275-140342

	mm	Stiche/min Stitches/min Points/min		Transportlänge Feeding length Long. d'entraînement			Nähgut Material Matière	
		max.	ab Werk ex factory à partir de l'usine	O	V	U		
275-140342	4	5000	4800	8	4	4	L, M, S	●
275-142342	4	5000	4800	8	4	4	L, M, S	●




L = Leicht  
M = Mittelschwer  
S = Schwer  
V = Vorwärts  
R = Rückwärts  
O = Obertransport  
U = Untertransport  
● = Serienmäßig  
○ = Zusatzausstattung

L = Lightweight  
M = Medium weight  
S = Heavy weight  
V = Forwards  
R = Backwards  
O = Top feed  
U = Bottom feed  
● = Standard equipment  
○ = Optional equipment






275-140342	●	●	●	○	○	●
275-142342	●	●	●	○	○	●

			Abmessungen Dimensions Dimensions			 - System
	C	D	Länge Length Longeur [mm]	Breite Width Largeur [mm]	Höhe Height Hauteur [mm]	
	[mm]	[mm]				
275-140342	285	115	1060	500	1700	797
275-142342	285	115	1060	500	1700	797





  

	 - Nm		Synthetik Synthetic Synthétique		Baumwolle Cotton Coton
275-140342	70 - 120	max. 30/3	max. 20/3		
275-142342	70 - 120	max. 30/3	max. 20/3		

				
Eine Nadel Single needle Une aiguille	Doppelsteppstich Double lockstitch Point noué	Horizontalgreifer, klein Horizontal hook, small Crochet vertical, petit	Unter- und differenzierbarer Fuß-Obertransport Bottom feed and variable foot top feed Entraînement inférieur et supérieur par pied var.	Fadenabschneider unter der Stichplatte Tread cutter below the throat plate Coupe-fil sous la plaque à aiguille

			
Funktion fuß-/hand-/kniebetätigt Function pedal-/hand-/knee-controlled Commande à pédale/à la main/à genouillère	Nahtverriegelung, Fußlüftung, FA fußbetätigt Seam tacking, sew, foot lift, thread cut, pedal controlled Point d'arrêt, c-fil et lève pied commandés par pied	Mehrweite oben, über Stellrad Fullness above, by setting wheel Embu en haut réglé par roue	Mehrweite oben, über Steuerung Fullness above, by fullness control Embu en haut réglé par commande d'embu

### 275-140342: Application Illustrations



