

## Interlock stitch machines

### FW600 Series



Max. Speed: 4500 rpm

Stitch length adjustment: Crank

Diff. feed ratio adjustment: Lever

Subclass					
Fabric thickness	Subclasses	Number of needles	Number of threads	Needle space	Seam width
~	FW603FB	2, 3	3-5	3.2• 4.0• 4.8• 5.6mm	—
~	FW603GB	2, 3	3-5	3.2• 4.0• 4.8• 5.6mm	—

## Interlock stitch machines

### FW600 Series

#### Easy-to-operate small circumference cylinder bed

Most suitable for covering operations on seams of small cylindrical goods such as sleeve seams, sleeve openings or neck with reattached rib knit of sweat shirts, side seams of sweat pants, etc.

#### Provides accurate covering Equipped with the easy-to-adjust needle plate fabric guide

The garments can be guided more easily and securely due to the fabric guide mounted on the needle plate, adjustable according to the thickness of the material (2.0mm ? 4.0mm).

- \* Equipped with HR device
- \* Differential feed adjustment lever
- \* Stitch length adjustment crank

## Labor saving devices

Code	Device names	Descriptions
UT	Thread trimmer	A device for interlock stitch machines to trim threads. Threads are easily cuts, by pressing the treadle with the heel. Cuts fast the needle thread, looper thread and top cover thread when the pedal is heeled.