

Safety stitch machines

M832 Series



Max. Speed: 7000 rpm

Stitch length adjustment: Push-button

Diff. feed ratio adjustment: Lever

Subclass					
Fabric thickness	Subclasses	Number of needles	Number of threads	Needle space	Seam width
~	M832-355	3	6	3+2mm	4mm
~	M832-38	2	5	3mm	4mm
~	M832-70	2	5	5mm	5mm
~	M832-86	2	5	5mm	6mm

Safety stitch machines

M800 Series

A further advanced, best-selling model!

M800 Series, which was developed using all of PEGASUS' state-of -the-art technology, while maintaining cost effectiveness and quality, responds to various needs with a full line of subclasses.

Labor saving devices

code	Device names	Descriptions
TK	Tape cutter	These devices cut a tape and/or thread chain at the start and end of sewing. The cutter knife is lowered with the switch to cut the tape and/or thread chain. No scissors are needed. Two types of switches are available, finger and knee switches.
KH	Flat type vacuum chain cutter	A thread chain is cut as soon as it is sucked up by air suction. There is no need to cut the thread chain using scissors. The suction inlet is positioned flush with the needle plate and right behind the presser foot. Thanks to this feature, wide double chainstitch, extra heavy weight or woolen thread chains are smoothly sucked up.