

Double chainstitch machines

W522 Series



Max. Speed: 5000 rpm

Stitch length adjustment: Push-button

Diff. feed ratio adjustment: Lever

Subclass					
Fabric thickness	Subclasses	Number of needles	Number of threads	Needle space	Seam width
~	W522-04A	2	4	6.4、9.5mm	—
~	W522A-01	2	5	6.4mm	—

Double chainstitch machines

W522 Series

Reduces the number of operations from two to one

W522A-01x264/KH


* For attaching side pocket facing on pocket openings of men's wear, jeans, etc. This machine reduces the number of operations two to one. No other machine is needed for this operation, which previously required surging the facing and attaching it to the pocket on a lockstitch machine. One less operation means a great reducing both in time and labor, and an increase in output.

* Features special gauges, which make the machine easily adaptable to a variety of sewing conditions. Easy-to-thread looper thread guide slides to the operator with the lever, thus increasing productivity.

* Adjusting lever to adjust the differential feed push button to adjust the stitch length.

* Micro-adjusting screw on the looper holder can make a fine front-to-back adjustment on the lower looper.

* Optional flat type vacuum chain cutter sucks the thread chain down to trim neatly. This feature adds to the efficiency of the operation.



Offers a wider variety of applications

W522-04A

* In addition to attaching tape to flies on briefs, it permits you to more efficiently cover overlock seams on shoulders and neck openings of T-shirts with tape to increase applications.

* The flatbed provides larger working space making sewing operations easier on briefs and T-shirts.

* The maximum speed 5,000 rpm, fast machine dramatically increases production.

* Easy-to-use differential feed adjusting lever and stitch length adjusting push button.

* Optional Devices: TK320 (Pneumatic tape cutter) EF120 (Electric automatic elastic/tape feeder, vertical feeding type)