

Double chainstitch machines

W674 Series



Max. Speed: 4000 rpm

Stitch length adjustment: Dial

Diff. feed ratio adjustment: -----

Subclass

Fabric thickness	Subclasses	Number of needles	Number of threads	Needle space	Seam width
~	W674-40	4, 5	7, 9	—	—
~	W674-42	4	8	—	—
~	W674-45	4, 5	7, 9	—	—

Double chainstitch machines

W674 Series

“Super tuckers” are added to the W600 Series

Inserts, hems and attached elastic easily and neatly into/on waists of medium weight fabrics such as jogging trunks and sweat pants. With a full range of subclasses, you can select as required according to your needs.

Labor saving devices

Code	Device names	Descriptions
HG	Hemming guide	This sliding type-hemming guide folds the fabric to form a hem in hemming operations. Thanks to this device, hemming is easy and resulting hem width is uniform, so quality products are obtained. Two types of driving sources are available, pneumatic and electric.
UT	Thread trimmer	A device for interlock stitch machines to trim threads. Threads are easily cuts, by pressing the treadle with the heel. Cuts fast the needle thread, looper thread and top cover thread when the pedal is heeled.
RP	Rear puller	The roller pulls the fabric from behind the needle drop hole. Thanks to this device, the machine smoothly sews difficult-to-feed fabrics, providing beautifully finished products with no plyshifting.