

## Interlock stitch machines

### W700 Series



Max. Speed: 6000 rpm

Stitch length adjustment: Push-button

Diff. feed ratio adjustment: Lever

Subclass					
Fabric thickness	Subclasses	Number of needles	Number of threads	Needle space	Seam width
~	W762-01	2, 3	3-5	3.2, 4, 4.8, 5.6, 6.4mm	—
~	W762-02	2, 3	3-5	3.2, 4, 4.8, 5.6, 6.4mm	—
~	W762-03	2, 3	3-5	4, 4.8, 5.6, 6.4mm	—

## Interlock stitch machines

### W700 Series

#### Short bed type is the most suitable machine for covering

With only 3 cm from the bed side to the needle drop, this short bed machine with particular emphasis on delivering best performance in covering operation is most suitable for covering.

#### Steplessly adjustment stitch length

To adjust the stitch length, just press the push-button to turn the pulley. Since it can be steplessly adjustable, the optimum stitch length can be obtained according to fabrics and processes.

#### Large size lever provided for easy differential feed ratio adjustment

The large size lever located on the right side no to obstruct the operator provides ease of operation. The differential feed ratio can be changed during the operation (intermittently) to provide partial ruffling at a touch.

- \* HR device (standard equipment)
- \* Equipped with the oil filter

#### To modify subclass, replace the cover and gauge parts

Basically, all you have to do is to replace the cover and gauge parts to modify the subclasses to be intended for various processes. (Expect the binder for tape binding and the hemming guide for hemming.)

### Labor saving devices

Code	Device names	Descriptions
TK	Tape cutter	These devices cut a tape and/or thread chain at the start and end of sewing. The cutter knife is lowered with the switch to cut the tape and/or thread chain. No scissors are needed. Two types of switches are available, finger and knee switches.
UT	Thread trimmer	A device for interlock stitch machines to trim threads. Threads are easily cuts, by pressing the treadle with the heel. Cuts fast the needle thread, looper thread and top cover thread when the pedal is heeled.