

FW787T-356/EWT/F FW787T-356/EAT/F

CYLINDER BED COVERING STITCH MACHINE WITH THREAD TRIMMER,
TUBULAR ELASTIC WAIST BAND ATTACHMENT (MINI SERVO MOTOR)



Feature:

- "Clamp Type" knee switch which don't need to cut the table, drilling hole, install by screw. It's easy to fix them up.
- The special design of "Folding Type" connect lever which will easy for you to open the front cover conveniently & promptly.
- Our precise production which to offer you more smoothly operation & seams.










The top thread trimmer could follow the users requested to adjust any precise cutting angle.

The patented structure provides stable cutting and easy maintenance. The special design under trimmer plunger, to micro-adjust the length of blade precisely when it cutting.

The first design, patent awarded "Direct Driving Under Shaft Connecting Type" mini servo motor that could offer you easy to installation, more sensitive, more silence and precisely needle position detection. The machine head wouldn't swing when it begin sewing & stopping.

- First, To develop the patent of "Direct Driving Type" Presser Foot Lifter. It's going to more sensitive and silent.
- "Horn type" regulating fabrics guide, to offer stable covering stitch.
- Adjustable piping hemmer, offer-hemming function.
- The micro stitch length-regulating lever, which could adjust the stitch length easily.
- Only change the gauge set & attachment, which could use the binder of flat-bed machine to offer standard tape attaching. "Covering, Hemming & Taping", three basic functions in one m/c.
- The first design "inboard type synchronizer" for covering stitch machine which could complete solve the problems of synchronizer swing, difficult to setting, locating and adjustment...etc.
- The patented looper thread take-up put on the outside of body, to clean the winding and adjustment easily. The flexible thread take-up eyelet holder, to offer the looper thread tension and release more details adjustment.

Specification:

MODEL			 mm	 mm	 mm	 mm		AVAILABLE DEVICE
FW787T-240	2	3	1.4	4.0	7.0	0.8	4500	Q、F、L
FW787T-248	2	3		4.8				
FW787T-348	3	5		4.8				
FW787T-356	3	5		5.6				
FW787T-364	3	5		6.4				
FW787T-456	4	6		5.6				
FW787T-460	4	6		6.0				
FW787T-464	4	6	4.5	6.4		1.4		