

FW787T-356/EWT/L1&L2 FW787T-356/EAT/L1&L2

CYLINDER BED COVERING STITCH MACHINE WITH THREAD TRIMMER,
REAR PULLER, MINI SERVO MOTOR



Feature:

The top thread trimmer could follow the users requested to adjust any precise cutting angle.

The patented structure provides stable cutting and easy maintenance. The special design under trimmer plunger, to micro-adjust the length of blade precisely when it cutting.










The first design, patent awarded "Direct Driving Under Shaft Connecting Type" mini servo motor which could offer you easy to installation, more sensitive, more silence and precisely needle position detection. The machine head wouldn't swing when it begin sewing & stopping.



To extend the Length of Lower Feed Roller. To offer you more stable feeding, Low Breakdown and easy to repair. The machine speed doesn't disturb the stitch length.

- First, To develop the patent of "Direct Driving Type" Presser Foot Lifter. It's going to more sensitive and silent.
- "Horn type" regulating fabrics guide, to offer stable covering stitch.
- Adjustable piping hemmer, offer-hemming function.
- The micro stitch length-regulating lever, which could adjust the stitch length easily.
- Only change the gauge set & attachment, which could use the binder of flatbed machine to offer standard tape attaching. "Covering, Hemming & Taping", three basic functions in one m/c.
- The first design "inboard type synchronizer" for covering stitch machine which could complete solve the problems of synchronizer swing, difficult to setting, locating and adjustment...etc.
- The patented looper thread take-up put on the outside of body, to clean the winding and adjustment easily. The flexible thread take-up eyelet holder, to offer the looper thread tension and release more details adjustment.

Specification:

MODEL								AVAILABLE DEVICE
FW787T-240	2	3	1.4	4.0	7.0	0.8	4500	Q、F、L
FW787T-248	2	3		4.8				
FW787T-348	3	5		4.8				
FW787T-356	3	5		5.6				
FW787T-364	3	5		6.4				
FW787T-456	4	6		5.6				
FW787T-460	4	6		6.0				
FW787T-464	4	6	4.5	6.4		1.4		