


FW787T

CYLINDER BED COVERING STITCH MACHINE (MINI SERVO MOTOR)



Feature:

The first design, patent awarded "Direct Driving Under Shaft Connecting Type" mini servo motor which could offer you easy to installation, more sensitive, more silence and precisely needle position detection. The machine head wouldn't swing when it begin sewing & stopping.



- First, To develop the patent of "Direct Driving Type" Presser Foot Lifter. It's going to more sensitive and silent.
 - "Horn type" regulating fabrics guide, to offer stable covering stitch.
 - Adjustable piping hemmer, offer-hemming function.
 - The micro stitch length-regulating lever, which could adjust the stitch length easily.
 - Only change the gauge set & attachment, which could use the binder of flat-bed machine to offer standard tape attaching. "Covering, Hemming & Taping", three basic functions in one m/c.
 - The first design "inboard type synchronizer" for covering stitch machine which could complete solve the problems of synchronizer to swing, difficult to setting, locating and adjustment...etc.
- The patented looper thread take-up put on the outside of body, to clean the winding and adjustment easily. The flexible thread take-up eyelet holder, to offer the looper thread tension and release more details adjustment.

Specification:

MODEL								AVAILABLE DEVICE
FW787T-240	2	3	1.4	4.0	7.0	0.8	4500	EST EWT Q、F、L
FW787T-248	2	3		4.8				
FW787T-348	3	5		4.8				
FW787T-356	3	5		5.6				
FW787T-364	3	5		6.4				
FW787T-456	4	6		5.6				
FW787T-460	4	6		6.0				
FW787T-464	4	6	4.5	6.4		1.4		