



SC-7200 SC-1720

DOUBLE NEEDLE, PICOT-STITCH, FLATBED SEWING MACHINE.



↑
SC-7200

↑
SC-1720

Click picture see the sample

Max Sewing Speed: 2,500 S.P.M.

Picot-Stitch Length: 3~5mm

Needle Bar Stroke: 33.4mm (Picot-Stitch Needle)
16.5mm (Rear Base Needle)
33.4mm (Front Guiding Needle)

The Lifting of Presser Foot Bar: 5mm

Needle System: HA x 1 (Picot-Stitch Needle)
PKG x 8 (Front Guiding Needle)
PKZ x 1 (Rear Base Needle)

FEATURES:

- ◆ Applied with the timing belt for connecting upper shaft and lower shaft, so even in high-speed running, the machine is still running smoothly and noiselessly.
- ◆ Simply adjusted the adjusting rod, could change the feeding volume of feed dog easily.
- ◆ The presser foot bar mechanism with special function of automatic lifting, so the machine is very suitable for the curve picot-stitching.
- ◆ The uniform and beautiful picot-stitch seams, ensured the high quality products.
- ◆ High efficiency and wide usability for blouse, shirt, dress, necktie, towel, handkerchief, tablecloth, sheet,...etc.