

HIGH POST BED COMPOUND FEED LOCKSTITCH SEWING MACHINE



TK-1247HL
1NEEDLE, LEFT-SIDE HOOK



TK-1247HR
1-NEEDLE, RIGHT-SIDE HOOK



TK-1247SHL
1NEEDLE, SLENDER POST BED
LEFT-SIDE HOOK



TK-1247SHR
1-NEEDLE, SLENDER POST BED
RIGHT-SIDE HOOK



TK-1247HBL
1NEEDLE, LEFT-SIDE HOOK



TK-1247HBR
1-NEEDLE, RIGHT-SIDE HOOK



TK-1248HB
2-NEEDLE, BIG HOOK

7	1-Needle
8	2-Needle
TK-124 <input type="checkbox"/> H <input type="checkbox"/>	
L	Left-side hook
R	Right-side hook

SPECIFICATION

MAX. SPEED	: 1600 S.P.M.
POST BED HEIGHT	: 443MM
MAX STITCH LENGTH	: 6 MM
PRESSER FOOT LIFT	: 15 MM
NEEDLE BAR STROCK	: 36 MM
NEEDLE	: DPX17 #22
MOTOR	: 1/2H.P. CLUTCH MOTOR
N.W.	: 64 KGS
G.W.	: 100 KGS
MEASUREMENT	: 0.335 CBM

- HIGH POST BED AND COMPOUND FEED DESIGN SUTABLE FOR SEWING THREE-DIMENSIONAL ARTICLES SMOOTHLY SUCH AS BAG CAP. BOOTS. TETNS AND CUSHIONS ETC.
- BEING EQUIPPED WITH SPRING RETURN REVERSE LEVER TYPE FEED MECHANISM FOR CONVENIENT OPERATION.
- BIG HOOK NOT ONLY PROVIDES PERFECT UNIFORMED STITCHING BUT ALSO ASSURES EFFICIENT WORK.
- SPECIAL DESIGNED POST BED (TK1247SHL/TK1247SHR) SUITABLE FOR LIMITED CORNER STITCHING AND EXTRA TUBULOUS SLENDER ARTICLES.