

CYLINDER BED COMPOUND FEED HEAVY DUTY LOCKSTITCH SEWING MACHINE

THIS MACHINE IS SUITABLE FOR SEWING MEDIUM AND HEAVY MATERIALS AS WELL AS GENERAL LEATHER GOODS OF A WIDE RANGE FROM HANDBAG, LEATHER SHOES, TO SPORTS SHOES



TK-335 FOR BINDING SEWING

- FREE CYLINDER BED WHICH ENABLES EASY MOVEMENT OF BULKY OR TUBULAR WORKPIECES.
- EASY HANDLING EVEN ON MATERIALS WITH ROUGH, SLIPPERY OR TACKY SURFACES.
- SMOOTH SEWING WHEN JOINING SEVERAL PLIES OF DIFFERENT THICKNESS.
- SUITABLE FOR OUTSIDE PIPING OPERATION WHEN EQUIPPED WITH FOLDER ATTACHMEN.



TK-335N FOR NORMAL SEWING

SPECIFICATIONS:

| | |
|--------------|---------------------------|
| SPEED | : 2,000 S.P.M. |
| NEEDLE | : DP X 17 #14,16,18,20 |
| MOTOR | : 1/3H.P. CLUTCH MOTOR |
| N.W. | : 32 KGS |
| G.W. | : 34 KGS |
| MEASUREMENT: | 0.094 CBM |

CYLINDER BED COMPOUND FEED HEAVY DUTY LOCKSTITCH SEWING MACHINE

THIS MACHINE IS SUITABLE FOR SEWING MEDIUM/HEAVY THICKNESS LEATHER OR FABRIC PRODUCTS SUCH AS: HANDBAG, LEATHER SHOES SPORTING SHOES, AND GENERAL LEATHER PRODUCTS.



TK-341 FOR BINDING SEWING

- EASY HANDLING EVEN ON MATERIALS WITH ROUGH, SLIPPERY OR TACKY SURFACES.
- SMOOTH SEWING WHEN JOINING SEVERAL PLIES OF DIFFERENT THICKNESS.
- THE NARROW CYLINDER ARM WHICH ENABLE EASY OPERATION ON TUBULAR AND CONCAVE WORKPIECES.
- SUITABLE FOR OUTSIDE PIPING OPERATION WHEN EQUIPPED WITH FOLDER ATTACHMENT.



TK-341N FOR NORMAL SEWING

SPECIFICATIONS:

| | |
|--------------|---------------------------|
| SPEED | : 2,000 S.P.M. |
| NEEDLE | : DP X 17 #14,16,18,20 |
| MOTOR | : 1/3H.P. CLUTCH MOTOR |
| N.W. | : 32 KGS |
| G.W. | : 34 KGS |
| MEASUREMENT: | 0.094 CBM |

CYLINDER BED COMPOUND FEED HEAVY DUTY LOCKSTITCH SEWING MACHINE

THIS MACHINE IS SUITABLE FOR SEWING MEDIUM/HEAVY THICKNESS LEATHER OR FABRIC PRODUCTS SUCH AS: HANDBAG, LEATHER SHOES SPORTING SHOES, AND GENERAL LEATHER PRODUCTS.



TK-735 FOR BINDING SEWING

- EASY HANDLING EVEN ON MATERIALS WITH ROUGH, SLIPPERY OR TACKY SURFACES.
- SMOOTH SEWING WHEN JOINING SEVERAL PLIES OF DIFFERENT THICKNESS.
- THE NARROW CYLINDER ARM WHICH ENABLE EASY OPERATION ON TUBULAR AND CONCAVE WORKPIECES.
- SUITABLE FOR OUTSIDE PIPING OPERATION WHEN EQUIPPED WITH FOLDER ATTACHMENT.



TK-735N FOR NORMAL SEWING

SPECIFICATIONS:

| | |
|--------------|---------------------------|
| SPEED | : 2,000 S.P.M. |
| NEEDLE | : DP X 17 #14,16,18,20 |
| MOTOR | : 1/3H.P. CLUTCH MOTOR |
| N.W. | : 32 KGS |
| G.W. | : 34 KGS |
| MEASUREMENT: | 0.094 CBM |