

FLAT BED LOCKSTITCH SEWING MACHINE WITH WHEEL FEED NEEDLE FEED AND DRIVEN ROLLER PRESSER



SPECIFICATIONS:

SPEED	: 2,000 S.P.M.
NEEDLE	: DPX5 (#14,#16,#18,#20)
MOTOR	: 1/3H.P. CLUTCH MOTOR
N.W.	: 38 KGS
G.W.	: 40 KGS
MEASUREMENT	: 0.10 CBM

TK-551 SINGLE NEEDLE

UPPER ROLLER, LOWER WHEEL AND NEEDLE FEEDING MECHANISM ENSURE SMOOTH SEWING, CONTINUOUS SUPPLY OF ALL KINDS OF MATERIAL AND PROVIDES CONSTANT WORKING ABILITY.

NEEDLE FEEDING ENSURES CONSTANT SUPPLY OF THIN AND THICK MATERIAL NO MATTER IT MOVES STRAIGHT FORWARD OR MAKES TURNS.

ALSO SUITABLE FOR SEWING SPONGY MATERIAL, NO CRINKLE OR TRANSFORM WILL BE OCCURRED. INSTEAD THE STITCH IS VERY SMOOTH AND NEAT.

LOW FRICTION BETWEEN THE PARTS BECAUSE BALL AND NEEDLE BEARINGS ARE USED. EASY MAINTENANCE AND LONG SERVICE LIFE.