

## POST BED LOCKSTITCH SEWING MACHINE WITH WHEEL FEED NEEDLE FEED AND DRIVEN ROLLER PRESSER



**TK-591**  
SINGLE NEEDLE



**TK-592**  
DOUBLE NEEDLE

- UPPER ROLLER, LOWER WHEEL AND NEEDLE FEEDING MECHANISM ENSURE SMOOTH SEWING AT ALL TIMES EVEN WHEN JOINING OTHER MATERIAL FOR OVERLAP SEWING.
- NEEDLE FEEDING ENSURES CONSTANT SUPPLY OF THIN AND THICK MATERIAL NO MATTER IT MOVES STRAIGHT FORWARD OR MAKES TURNS.
- ALSO SUITABLE FOR SEWING SPONGY MATERIAL, NO CRINKLE OR TRANSFORM WILL BE OCCURRED, INSTEAD THE STITCH IS VERY SMOOTH AND NEAT.
- LOW FRICTION BETWEEN THE PARTS BECAUSE BALL AND NEEDLE BEARINGS ARE USED. EASY MAINTENANCE AND LONG SERVICE LIFE.

### **SPECIFICATIONS:**

MAX SPEED	: 2,500 S.P.M.
NEEDLE	: DP X 5 (#14,16,18,20)
MOTOR	: 1/3H.P. CLUTCH MOTOR
NET WEIGHT	: 52 KGS
GROSS WEIGHT	: 58 KGS
MEASUREMENT	: 0.16 CBM

## POST BED LOCKSTITCH SEWING MACHINE WITH WHEEL FEED NEEDLE FEED AND DRIVEN ROLLER PRESSER



**TK-691**  
SINGLE NEEDLE



**TK-692**  
DOUBLE NEEDLE

- UPPER ROLLER, LOWER WHEEL AND NEEDLE FEEDING MECHANISM ENSURE SMOOTH SEWING AT ALL TIMES EVEN WHEN JOINING OTHER MATERIAL FOR OVERLAP SEWING.
- NEEDLE FEEDING ENSURES CONSTANT SUPPLY OF THIN AND THICK MATERIAL NO MATTER IT MOVES STRAIGHT FORWARD OR MAKES TURNS.
- ALSO SUITABLE FOR SEWING SPONGY MATERIAL, NO CRINKLE OR TRANSFORM WILL BE OCCURRED, INSTEAD THE STITCH IS VERY SMOOTH AND NEAT.
- LOW FRICTION BETWEEN THE PARTS BECAUSE BALL AND NEEDLE BEARINGS ARE USED. EASY MAINTENANCE AND LONG SERVICE LIFE.

### **SPECIFICATIONS:**

MAX SPEED	: 2,500 S.P.M.
NEEDLE	: DP X 5 (#14,16,18,20)
MOTOR	: 1/3H.P. CLUTCH MOTOR
NET WEIGHT	: 52 KGS
GROSS WEIGHT	: 58 KGS
MEASUREMENT	: 0.16 CBM