

Color-60



Brand: TILO

Light sources: D65, TL84, CWF, F, UV, U30, A, TL83

Weight: 38Kg

Dimensions: 710x530x570 mm

Product info

Specifications

Order No.	Product name	Model No.	D65	TL84	CWF	F	UV	U30	A	TL83	Voltage
10108	color assessment cabinet (CAC)	Color-60 (220V)	2	2	2	4	1	2	2	2	220V/50Hz
10808	color assessment cabinet (CAC)	Color-60 (115V)	2	2	2	4	1	2	2	2	115V/60Hz

Optional fittings: Light source diffusing board / 45° normative stand / Lamp container.

Features:

- > Light source's running time display / Name display / Switching frequency display.
- > Auto conversion between light sources; Different spectrum with same color.
- > No need warm-up; No flicker; Color assessment quick and reliable.
- > Low power-consumption; No heat emission; Efficient illumination.
- > English/American standard light sources.
- > A and 30U light sources in American standard.
- > Light source's name is changeable.
- > High-level TAYOLE brand.

Light source:

D65 --- International-standard Artificial Daylight

Color temperature:6500K Power:20W

TL84 --- Applicable to stores in Europe, Japan and China

Color temperature:4000K Power:18W

CWF (Cool White Fluorescent)

Color temperature:4150K Power:20W

F-light ---- Referential color-comparing light; Applicable to family/hotel

Color temperature:2700K Power:40W

UV ---- Ultraviolet light source

Wavelength:365nm Power:20W

U30 (Warm White Fluorescent)

Color temperature:3000K Power:18W

A --- American style shooting light; Referential color-comparing light

Color temperature:2856K Power:60W

TL83 --- European standard warm-white store light source

Color temperature:3000K Power:18W