

P120 (Oversize)



Brand:TILO

Light sources:D65,TL84,CWF,F,UV,U30

Weight:60Kg

Dimensions:1310x600x800 mm

Product info

Specifications

| Order No. | Product name | Model No. | D65 | TL84 | CWF | F | UV | U30 | Voltage |
|-----------|--------------------------------|----------------------|-----|------|-----|---|----|-----|-----------|
| 10118 | Color assessment cabinet (CAC) | P120 Oversize (220V) | 2 | 2 | 2 | 4 | 1 | 2 | 220V/50Hz |
| 10818 | Color assessment cabinet (CAC) | P120 Oversize (115V) | 2 | 2 | 2 | 4 | 1 | 2 | 115V/60Hz |

Optional fittings: Light source diffusing board / 45° normative stand / Lamp container.

Features:

- > Light source's running time display / Name display / Switching frequency display.
- > Auto conversion between light sources; Different spectrum with same color.
- > No need warm-up; No flicker; Color assessment quick and reliable.
- > Low power-consumption; No heat emission; Efficient illumination.
- > Excellent English/American standard light sources.
- > To add a light source and to change a light source name are available.
- > Big cabinet room --- convenient and available for big objects.

Light source:

D65 --- International-standard Artificial Daylight

Color temperature:6500K Power:20W

TL84 --- Applicable to stores in Europe, Japan and China

Color temperature:4000K Power:18W

CWF (Cool White Fluorescent)

Color temperature:4150K Power:20W

F-light ---- Comparison referential light source, Applicable to family/hotel

Color temperature:2700K Power:40W

UV ---- Ultraviolet light source

Wavelength:365nm Power:20W

U30 (Warm White Fluorescent)

Color temperature:3000K Power:18W