

P60(6 light sources)



Brand:TILO

Light sources:

D65,TL84,CWF,F,UV,U30

Weight:35Kg

Dimensions:710x530x570 mm

Product info

Specifications

Order No.	Product name	Model No.	D65	TL84	CWF	F	UV	U30	Voltage
10107	Color assessment cabinet (CAC)	P60(6) standard (220V)	2	2	2	4	1	2	220V/50Hz
10807	Color assessment cabinet (CAC)	P60(6) standard (115V)	2	2	2	4	1	2	115V/60Hz

Optional fittings: Light source diffusing board / 45° normative stand / Lamp container.

Features:

- > Time running display of each light source.
- > Auto conversion between light sources; Different spectrum with same color.
- > No need warm-up; No flicker; Color assessment quick and reliable.
- > Low power-consumption; No heat emission; Efficient illumination.
- > Excellent English/American standard light sources.
- > To add a light source and to change a light source name are available.

Light source:

D65 --- International-standard Artificial Daylight

Color temperature:6500K Power:20W

TL84 --- Applicable to stores in Europe, Japan and China

Color temperature:4000K Power:18W

CWF (Cool White Fluorescent)

Color temperature:4150K Power:20W

F-light ---- Comparison referential light source, Applicable to family/hotel

Color temperature:2700K Power:40W

UV ---- Ultraviolet light source

Wavelength:365nm Power:20W

U30 (Warm White Fluorescent)

Color temperature:3000K Power:18W