

## T60 (5 light sources)



Brand: TILO  
Light sources: D65, TL84, CWF, F, UV

Weight: 30Kg

Dimensions: 710x405x570 mm

### Product info

#### Specifications

Order No.	Product name	Model No.	D65	TL84	CWF	F	UV	Voltage
10115	color assessment cabinet (CAC)	T60(5)standard (220V)	2	2	2	4	1	220V/50Hz
10815	color assessment cabinet (CAC)	T60(5)standard (115V)	2	2	2	4	1	115V/60Hz

Optional fittings: Light source diffusing board /45° normative stand / Lamp container.

#### Features:

- > Time running display of each light source.
- > Auto conversion between light sources; Different spectrum with same color.
- > No need warm-up; No flicker; Color assessment quick and reliable.
- > Low power-consumption; No heat emission; Efficient illumination.
- > English/American standard light sources.
- > Small volume; Convenient for use.

**Light source:**

**D65 --- International-standard Artificial Daylight**

Color temperature:6500K Power:20W

**TL84 --- Applicable to stores in Europe, Japan and China**

Color temperature:4000K Power:18W

**CWF (Cool White Fluorescent)**

Color temperature:4150K Power:20W

**F-light ---- Comparison referential light source, Applicable to family/hotel**

Color temperature:2700K Power:40W

**UV ---- Ultraviolet light source**

Wavelength:365nm Power:20W