



#### APPLICATIONS:

- For sewing medium & heavy weight materials such as textile, leather, vinyl, and various synthetics fabrics, etc.
- Suitable for sewing products as suitcase, sail, tents, luggage bags, leather clothes, leather products, etc.

#### FEATURES:

- Link feed mechanism, good durability and feed smoothly
- Gear oil pump lubrication system assures full lubrication even at a lower speed
- Big auto-lubrication hook and top and bottom feed improve the sewing efficiency
- Dial stopper assures same stitch length when forward or backward feed
- High presser foot lift height assures easy input and output of materials
- 3-bushing feed shaft, good rigidity and anti-wearness
- Automatic needle positioning, automatic stitch setting, auto-trimming, automatic reverse feed, automatic presser foot lift and other sewing modes
- Adjustable stitch length of forward and backward stitching, beautiful stitch

#### SPECIFICATIONS:

Model	Max. Sewing speed (s.p.m)	Max. Stitch length (mm)	Clearance under presser foot (mm)	Needle bar stroke (mm)	Needle (standard)
GC0302H-D2	2000	8	16 (by knee)	37	DP × 17 20 <sup>+</sup> -23 <sup>+</sup>
GC0302HCX-D2			8 (by hand)		DP × 17 25 <sup>+</sup>
Model	Amount of alternating presser foot lifter (mm)		Bed size (mm)	Working space (mm)	
GC0302H-D2	2-5		475 × 178	262 × 135	
GC0302HCX-D2	(standard 3.2)				