



GC6-6
GC6-6-1

GC6-6ZX

APPLICATIONS:

- For sewing light and medium-heavy materials, such as fabric, leather, jeans, synthetics, etc.
- Suitable for sewing such products as suitcase, tents, cushion, clothes, gloves, shoes, cap, leather products, bamboo matting, etc.

FEATURES:

- Single straight needle, link take-up thread
- Top and bottom feed to avoid the slippage between the different materials layers
- Long stitch length, large hook
- Good sewing capacity ability
- Wide application, long machine life
- Can keep same stitch length between forward and reverse stitching (GC6-6-1)
- No reverse feed, extra long stitch length(GC6-6ZX)

SPECIFICATIONS:

Model	Max. Sewing speed (s.p.m)	Max. Stitch length (mm)	Clearance under presser foot (mm)	Needle bar stroke (mm)	Needle (standard)
GC6-6	2000	9	6.5 (by hand)	37	DP×17 18 ² ~24 ²
GC6-6-1		6	13 (by knee)		
GC6-6ZX	1200	12	13 (by knee) 6.5 (by hand)		DP×17 23 ² ~25 ²
Model	Amount of alternating presser foot lifter (mm)	Lubrication system	Bed size (mm)	Working space (mm)	
GC6-6	2~5 (standard 3.2)	Oiled by hand	475×178	260×120	
GC6-6-1					
GC6-6ZX					