



TW2-B845-3



TW2-B845-5

APPLICATIONS:

- For sewing light, medium & heavy materials such as fabric, vinyl, synthetics, etc.
- Suitable for sewing such products as shirt, uniform, jeans, jacket, decorative, etc

FEATURES:

- Auto-lubrication, sliding thread take-up
- Arm shaft and hook shaft are supported by ball bearing, synchronized toothed belt driving
- Timing feed of needle bar and feed dog
- Double vertical auto-lubricating rotary hook
- Designed with split needle bar mechanism suitable for corner sewing
- Knob-type stitch length regulator and lever-type forward and backward feeding mechanism

SPECIFICATIONS:

Model	Max. Sewing speed (s.p.m)	Max. Stitch length (mm)	Clearance under presser foot (mm)	Needle bar stroke (mm)	Needle (standard)
TW2-B845-3	3000	4	10 (by knee)	33.4	DP×5 11 [#] ~16 [#]
TW2-B845-5		5	7 (by hand)		DP×5 14 [#] ~22 [#]

Model	Needle gauge	Bed size (mm)	Working space (mm)
TW2-B845-3	6.4 (standard)	518×178	244×95
TW2-B845-5			

OPTIONAL NEEDLE GAUGE:

Needle gauge	3.2mm 1/8"	4.0mm 5/32"	4.8mm 3/16"	7.9mm 5/16"	9.5mm 3/8"	12.7mm 1/2"	15.9mm 5/8"
TW2-B845-3	★	★	★	★	★	★	★
TW2-B845-5	★	★	★	★	★	★	★