



TW2-B872-3



TW2-B872-5

APPLICATIONS:

- For various materials such as fabric, vinyl, synthetics, etc.
- Suitable for sewing such products as shirt, uniform, jeans, jacket, decorative, etc

FEATURES:

- Auto-lubrication, sliding thread take-up
- Arm shaft and hook shaft are supported by ball bearing, synchronized toothed belt driving
- Timing feed of needle bar and feed dog
- Double vertical auto-lubricating rotary hook
- Knob-type stitch length regulator and lever-type forward and backward feeding mechanism

SPECIFICATIONS:

| Model | Max. Sewing speed (s.p.m) | Max. Stitch length (mm) | Clearance under presser foot (mm) | Needle bar stroke (mm) | Needle (standard) |
|------------|---------------------------|-------------------------|-----------------------------------|------------------------|---------------------------------------|
| TW2-B872-3 | 3000 | 7 | 10 (by knee) | 33.4 | DP×5 11 [#] ~16 [#] |
| TW2-B872-5 | | | 7 (by hand) | | DP×5 14 [#] ~22 [#] |
| Model | Needle gauge | | Bed size (mm) | Working space (mm) | |
| TW2-B872-3 | 6.4 (standard) | | 518×178 | 244×95 | |
| TW2-B872-5 | | | | | |

OPTIONAL NEEDLE GAUGE:

| Needle gauge | 3.2mm 1/8" | 4.0mm 5/32" | 4.8mm 3/16" | 7.9mm 5/16" | 9.5mm 3/18" | 12.7mm 1/2" | 15.9mm 5/8" |
|--------------|---------------|----------------|----------------|----------------|----------------|----------------|----------------|
| TW2-B872-3 | ★ | ★ | ★ | ★ | ★ | ★ | ★ |
| TW2-B872-5 | ★ | ★ | ★ | ★ | ★ | ★ | ★ |